



**CAG Federal**  
Service Disabled Veteran Owned Small Business (SDVOSB)

# Top Sellers Product Catalog

521

*Products for a safer, cleaner, and more sustainable world.*

Spill Containment • Stormwater Management • Facility Protection

BEST IN  
INDUSTRY  
**5 YEAR  
WARRANTY**



## Ultra-Spill Pallet Plus Model® PAGE 2

Also pictured: Ultra-Overpack (pg 7), Ultra-Utility Tray (pg 4),  
Ultra-Spill Deck (pg 3)

## Ultra-Spill Pallet®



Spill Containment Pallets protect against chemical spills or leaks

- + High load capacities – up to 6,000 lbs. for 4-Drum Model, 3,000 lbs. for 2-Drum Model.
- + Removable grating makes clean-up quick and easy.
- + 100% polyethylene construction – compatible with a broad range of chemicals, including acids and corrosives.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



1000



2504

Part#	Description	Dimensions in. (mm)	Uniformly Dist. Load lbs. (kg)	Contain. Cap. gal. (L)	Weight lbs. (kg)
1010	P2 Standard (2-Drum)	53 x 29 x 16.5 (1,347 x 737 x 420)	3,000 (1,361)	66 (250)	63.0 (29.0)
1000	P4 Standard (4-Drum)	53 x 53 x 11.8 (1,347 x 1,347 x 299)	6,000 (2,722)	66 (250)	90.0 (41.0)
2504	P2 Economy (2-Drum)	53 x 29 x 16.5 (1,347 x 737 x 420)	1,200 (544)	66 (250)	63.0 (29.0)
1112	P4 Economy (4-Drum)	53 x 53 x 11.8 (1,347 x 1,347 x 299)	3,000 (1,361)	66 (250)	85.0 (39.0)
0678	P4 Ramp - Non-slip, Polyethylene & Steel	68.5 x 28.5 x 12 (1,740 x 724 x 305)	700 (318)	-	74.0 (34.0)

Also available with drain

## Ultra-Spill Pallet Nestable Model®



Low-profile, nestable spill pallet reduces shipping costs and storage space

- + Large, 66-gallon sump captures leaks and spills from steel or poly drums (4 drum capacity).
- + Nestable design allows multiple pallets to be shipped (or stored) in a minimal amount of space.
- + 100% polyethylene construction – compatible with a broad range of chemicals, including acids and corrosives.
- + Low-profile (10" height) makes drum handling safer and easier.
- + 2-way forkliftable – provides easy positioning and relocation.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



1230



Part#	Description	Dimensions in. (mm)	Uniformly Dist. Load lbs. (kg)	Contain. Capacity gal. (L)	Weight lbs. (kg)
1230	Nestable (4-Drum)	51 x 51 x 10 (1,295 x 1,295 x 254)	6,000 (2,722)	66 (250)	80.0 (36.0)
0676	Ramp - Polyethylene & Steel	55.5 x 28.5 x 8.8 (1,410 x 724 x 222)	700 (318)	—	43.0 (19.5)

Also available with drain

## Ultra-Spill Pallet Plus Model®



Combine high-strength and low-profile features while meeting EPA container storage regulations

- + Low profile positions drum funnels below eye level – significantly reduces the potential for hazardous fluids to splash into the eyes or face.
- + Nearly 50% lower than standard spill pallets. Drum handling is safer and less strenuous.
- + Forkliftable, all-polyethylene construction.
- + Removable grates feature a non-slip surface.
- + Available in 1, 2, 3, and 4-drum configurations.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



9630

0676 (Ramp)

Part#	Description	Dimensions in. (mm)	Uniformly Distributed Load lbs. (kg)	Contain. Capacity gal. (L)	Weight lbs. (kg)
9606	P1 Plus (1-Drum)	40 x 40 x 12 (1,016 x 1,016 x 305)	800 (363)	62 (235)	51.0 (23.0)
9610	P2 Plus (2-Drum)	65.5 x 40 x 8.8 (1,664 x 1,016 x 222)	4,500 (2,041)	66 (250)	88.0 (40.0)
9626	P3 Plus (3-Drum)	83 x 34.5 x 8.8 (2,108 x 876 x 222)	4,500 (2,041)	66 (250)	90.0 (41.0)
9630	P4 Plus (4-Drum)	62 x 62 x 8.8 (1,575 x 1,575 x 222)	9,000 (4,082)	75 (284)	140.0 (63.5)
0678	P1 Ramp	68.5 x 28.5 x 12 (1,740 x 724 x 305)	700 (318)	-	74.0 (34.0)
0676	P2, P3 & P4 Ramp	55.5 x 28.5 x 8.8 (1,410 x 724 x 222)	700 (318)	-	43.0 (19.5)

Also available with drain

## Ultra-Hard Top Plus Model®



Store hazardous drums safely outdoors with pumps and funnels in place

- + Tall 23 3/4" head space easily accommodates rotary drum pumps and large conical funnels.
- + Low profile (8 3/4") containment pallet positions drum-top funnels at a safe, convenient level to pour hazardous wastes.
- + 100% polyethylene construction will not rust or corrode.
- + Meets SPCC and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.
- + Helps meet Stormwater Management Regulations – NPDES, 40 CFR 122.26 (1999).



9612

Part#	Description	Dimensions in. (mm)	Uniformly Dist. Load lbs. (kg)	Contain. Capacity gal. (L)	Weight lbs. (kg)
9640	P1 Plus (1-Drum)	36 x 36 x 66 (915 x 915 x 1,677)	800 (363)	70 (265)	75.0 (34.0)
9612	P2 Plus (2-Drum)	67.3 x 41.3 x 7.4 (1,708 x 1,047 x 1,880)	4,500 (2,041)	66 (250)	260.0 (118.0)
9636	P4 Plus (4-Drum)	64.5 x 62 x 7.9 (1,638 x 1,575 x 2,007)	9,000 (4,082)	75 (284)	440.0 (200.0)
0676	*Ramp - Polyethylene & Steel	55.5 x 28.5 x 8.8 (1,410 x 724 x 222)	700 (318)	—	43.0 (19.5)

Also available with drain & additional configurations available

\*for P2 and P4 only



## Ultra-Spill Deck®



Low profile, modular spill decks allow you to design and create a containment system that meets your specific needs

- + Ultra-Spill Decks are available in 1, 2, and 4-drum modules. Modules are easily connected together with bulkhead fittings to allow a virtually unlimited number of customized configurations.
- + The bulkhead fittings not only “lock” connected modules together, but allow spilled liquid to flow from one module to the next.
- + Applications include hazardous waste collection, storage of virgin chemicals, drum dispensing, and battery storage.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



Shown above — 12-Drum Spill Deck System using the following components: (3) P4 Spill Decks – Part# 1072, (4) Bulkhead Fittings – Part# 1073, (4) T-Strips – Part# 1131 and (1) Ramp – Part# 1089. (Rack, drums and buckets are application props and are not included.)

Part#	Description	Dimensions in. (mm)	Uniformly Dist. Load lbs. (kg)	Contain. Capacity gal. (L)	Weight lbs. (kg)
1321	Spill Deck P1 Module	25.9 x 25.9 x 5.8 (657.4 x 657.4 x 146.1)	1,500 (681)	11 (42)	23.0 (10.0)
1086	Spill Deck P2 Module	52 x 25.9 x 5.8 (1,321 x 657 x 146)	3,000 (1,361)	22 (83)	40.0 (18.0)
1072	Spill Deck P4 Module	52 x 52 x 5.8 (1,321 x 1,321 x 146)	6,000 (2,722)	44 (167)	70.0 (32.0)
1089	Spill Deck Ramp	32 x 24 x 5.8 (812.8 x 609.6 x 146.1)	600 (272)	-	17.0 (8.0)

## Ultra-IBC Spill Pallet Plus®



Economical and portable containment for IBCs

- + Low profile, 28” overall height— allows safe and convenient IBC tank handling and dispensing.
- + All polyethylene construction — offers excellent chemical resistance and will not rust or corrode.
- + Low-cost design with value-added features and benefits.
- + Available with optional Bucket Shelf (Part# 1160) — catches leaks or spills during dispensing.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



1160 (Shelf)

Part#	Description	Dimensions in. (mm)	Load Cap. lbs. (kg)	Containment Cap. gal. (L)	Weight lbs. (kg)
1157	IBC Spill Pallet Plus	62 x 62 x 28 (1,575 x 1,575 x 711)	8,500 (3,856)	365 (1,382)	324.0 (147.0)
1160	Bucket Shelf	19.5 x 16 x 14.5 (495 x 406 x 368)	-	-	10.0 (5.0)

Also available with drain

## Ultra-Spill Deck Bladder System®



Hidden containment bladder automatically unfurls to capture large spills or drum leaks

- + Compact footprint saves valuable floor space — perfect for drum waste collection usage.
- + Use the Spill Deck Bladder Systems in place of taller containment pallets — low 5 3/4” deck height offers significant safety and handling benefits.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



2329

Part#	Description	Dimensions in. (mm)	Load Capacity lbs. (kg)	Contain. Capacity gal. (L)	Weight lbs. (kg)
1320	P1 Bladder System (1-Drum)	30.5 x 25.9 x 5.8 (774.7 x 657.4 x 146.1)	1,500 (681)	77 (291)	27.0 (12.0)
2329	P2 Bladder System (2-Drum)	52 x 30.5 x 5.8 (1,320.8 x 774.7 x 146.1)	3,000 (1,361)	88 (333)	44.0 (20.0)
2330	P4 Bladder System (4-Drum)	56.6 x 52 x 5.8 (1,438.4 x 1,320.8 x 146.1)	6,000 (2,722)	110 (416)	66.0 (30.0)
2317	Bladder Attachment (bladder and bulkhead)	25.9 x 4.6 x 4.6 (657.86 x 117.6 x 117.6)	-	66 (250)	4.0 (2.0)
6340	Replacement Bladder (for P/N 2317)	65.5 x 66 Unfurled (1,664 x 1,676)	-	66 (250)	2.0 (1.0)
2345	Bladder Pump	12 x 7 x 5.5	-	-	3.0 (1.5)

## Ultra-IBC Hard Top®



Comply with regulations while storing IBC tanks outdoors

- + Upper roll-top door and lower swingout doors combine to allow easy and convenient access to IBC.
- + Forkliftable and lockable.
- + Helps meet Stormwater Management Regulations — NPDES, 40 CFR 122.26 (1999).
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



1148

1162

Part#	Description	Dimensions in. (mm)	Load Cap. lbs. (kg)	Containment Cap. gal. (L)	Weight lbs. (kg)
1162	IBC Hard Top	64.5 x 62 x 96 (1,639 x 1,575 x 2,439)	8,500 (3,856)	365 (1,382)	525.0 (239.0)
1148	Twin IBC Hard Top	128 x 67 x 96 (3,251 x 1,702 x 2,438)	8,000 (3,629)	535 (2,025)	1,067.0 (484.0)

Also available with drain

## Ultra-Containment Sump®

MADE IN USA

BEST IN INDUSTRY  
5 YEAR  
WARRANTY

Eco-Smart

Rigid secondary containment for fuel tanks

- + Economical containment for 275, 500/550, and 1000-gallon fuel and oil tanks.
- + 100% polyethylene construction will not rust or corrode; provides superior chemical and weather resistance.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



2823



2800



2830

Part#	Description	Outside Dimensions in. (mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
2800	275 Sump	84.5 x 43.8 x 29 (2,146.3 x 1,111.3 x 736.6)	360 (1,363)	90.0 (41.0)
2823	550 Sump	90 x 61 x 32.8 (2,286 x 1,549.4 x 831.9)	605 (2,291)	108.0 (41.0)
2830	1000 Sump	149 x 64 x 33 (3,784.6 x 1,625.6 x 838.2)	1,100 (4,164)	244.0 (111.0)

Also available with drain

## Ultra-Drip Diverter®

Catch roof leaks and divert them away from equipment, inventory, and personnel

- + Large, vinyl-coated fabric catches roof leaks and channels them to standard hose hook-up. (Hoses available)
- + Hose can then be directed to proper drainage point.
- + Bottom fitting connects to a standard garden hose (optional), allows fluids to be collected in a drum or tank.
- + Rugged, coated vinyl construction.



1785



1780

Part#	Description	Dimensions ft. (mm)	Weight lbs. (kg)
1785	Roof Drip Diverter	5 x 5 (1,524 x 1,524)	2.0 (1.0)
1786	Roof Drip Diverter	7 x 7 (2,134 x 2,134)	4.0 (2.0)
1787	Roof Drip Diverter	10 x 10 (3,048 x 3,048)	8.0 (3.5)
1788	Roof Drip Diverter	12 x 12 (3,658 x 3,658)	15.0 (7.0)
1789	Roof Drip Diverter	15 x 15 (4,572 x 4,572)	22.0 (10.0)
1790	Roof Drip Diverter	20 x 20 (6,096 x 6,096)	36.0 (16.0)
1780	Pipe Drip Diverter	18 dia. x 18 (46 x 46)	2.0 (1.0)

## Ultra-Sidewinder® Cable Protection System

MADE IN USA

VIDEO ONLINE

Protect cords and cables and avoid dangerous tripping hazards

- + Articulating pieces offer flexible design - curves, corners, and s-curves are easily made while maintaining a completely flat profile.
- + Modular design makes it easy to reconfigure, repair, and replace targeted segments, even while the cable remains connected.
- + Available in small, medium, and large sizes.
- + Small size system (with cord in place) can be coiled for easy portability and transport.
- + Fully customizable length - from 4.5" to an unlimited length.



1802

1800 1830 1840

Patents: See [www.ultratechpatents.com](http://www.ultratechpatents.com)

Part#	Size	Color	Description	Dimensions in. (mm)	Weight lbs. (kg)
1800	Small	Black & Yellow	System w/ Endcaps	39.5 x 3 x .8 (1,003.3 x 76.2 x 19.1)	1.5 (0.7)
1802	Small	Black	System w/ Endcaps	39.5 x 3 x .8 (1,003.3 x 76.2 x 19.1)	1.5 (0.7)
1830	Medium	Black & Yellow	System w/ Endcaps	33 x 9.8 x 1.4 (838.2 x 247.7 x 35.1)	6.0 (2.7)
1840	Large	Black & Yellow	System w/ Endcaps	34 x 13.6 x 2.1 (863.6 x 346.2 x 54.1)	13.5 (6.0)

Extensions and additional sizes also available

## Ultra-Utility Tray®

MADE IN USA

Keep messy drips and spills off warehouse and factory floors

- + Heavy-duty polyethylene construction — will not rust or corrode.
- + Ribbed bottom keeps cans, pails and other containers elevated above small spills or leaks.
- + Nestable for easy storage when not in use.

BEST IN INDUSTRY  
5 YEAR  
WARRANTY

Eco-Smart



1034

1035

1031

1036

Part#	Dimensions in. (mm)	Containment Cap. gal. (L)	Weight lbs. (kg)
1031	Outside: 52.3 x 16.3 x 5 (1,327.2 x 412.8 x 127) Inside: 48 x 12 x 4.75 (1,219.2 x 304.8 x 120.65)	12 (45)	7.0 (3.5)
1032	Outside: 52.3 x 28.3 x 5 (1,327.2 x 717.6 x 127) Inside: 48 x 24 x 4.75 (1,219.2 x 609.6 x 120.65)	24 (91)	11.0 (5.0)
1033	Outside: 52.3 x 34.3 x 5 (1,327.2 x 870 x 127) Inside: 48 x 30 x 4.75 (1,219.2 x 762 x 120.65)	30 (113)	12.0 (5.5)
1034	Outside: 40.3 x 28.3 x 5 (1,022.4 x 717.6 x 127) Inside: 36 x 24 x 4.75 (914.4 x 609.6 x 120.65)	18 (68)	8.0 (3.5)
1035	Outside: 40 x 40 x 5 (1,016 x 1,016 x 127) Inside: 36 x 36 x 4.75 (914.4 x 914.4 x 120.65)	27 (102)	11.0 (5.0)
1036	Outside: 52 x 44 x 4 (1,320.8 x 1,117.6 x 101.6) Inside: 48 x 40 x 3.5 (1,219.2 x 1,016 x 88.9)	30 (113)	14.0 (6.5)

Flexible model also available

## Ultra-Containment Berm® Ultimate Model

Unique, “living hinge” design allows hands-free drive In/drive out — no need to manually raise or lower the endwalls

- + Once a vehicle has entered or exited, the walls automatically spring back to their vertical position.
- + Standard material of construction is Copolymer 2000™ (28 oz.). Other rugged, chemical resistant materials available.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



Part#	Dimensions ft. (m)	Containment Capacity gal. (L)	Weight lbs. (kg)
8505	12 x 60 x 1 (3.7 x 18.3 x 0.3)	5,385 (20,382)	309.0 (140)
8506	15 x 50 x 1 (4.6 x 15.2 x 0.3)	5,610 (21,234)	326.0 (148)
8507	15 x 66 x 1 (4.6 x 20.1 x 0.3)	7,405 (28,028)	405.0 (184)

8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts) See website

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand - See website

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)

## Ultra-Containment Berm® Foam Wall Model

Low profile design is perfect for equipment maintenance and portable drum containment

- + Capture nuisance leaks and spills from vehicles, oily equipment, tanks and drums.
- + No set-up required - simply unfold for quick deployment. Folded units require minimal storage space.



+ Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.

+ Custom sizes and sidewall height available.

Copolymer 2000™ Part#	PVC 22 oz. Part#	Dimensions ft. (m) Wall Height: 4 in. (102 mm)	Containment Capacity gal. (L)	Copolymer 2000™ Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8570	8460	4 x 6 (1.2 x 1.8)	59 (223)	27.0 (12.0)	21.0 (9.5)
8571	8461	8 x 8 (2.4 x 2.4)	159 (602)	45.0 (20.0)	40.0 (18.0)
8573	8471	10 x 20 (3.0 x 6.1)	498 (1,885)	101.0 (46.0)	83.0 (38.0)
8578	8462	12 x 16 (3.7 x 4.9)	478 (1,809)	97.0 (44.0)	74.0 (33.5)
8581	8463	12 x 35 (3.7 x 10.7)	1,047 (3,963)	184.0 (84.0)	138.0 (62.5)
8583	8464	12 x 50 (3.7 x 15.2)	1,496 (5,663)	249.0 (113.0)	187.0 (85.0)

8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts) See website

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand - See website

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)

## Ultra-Containment Berm® Collapsible Model

Economical design sets up quickly — provides secure containment

- + The Collapsible Wall Model Containment Berm features rugged PVC sidewall assemblies for sidewall support. Simply swivel the “feet” of the PVC supports to lower or raise the sidewalls in just seconds!
- + Standard material of construction is Copolymer 2000™ (28 oz.). Other rugged, chemical resistant materials available.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



Part#	Dimensions ft. (m)	Containment Capacity gal. (L)	Weight lbs. (kg)
8405	4 x 6 x 1 (1.2 x 1.8 x 0.3)	179 (678)	43.0 (19.5)
8403	6 x 6 x 1 (1.8 x 1.8 x 0.3)	269 (1,018)	46.0 (21.0)
8400	10 x 10 x 1 (3 x 3 x 0.3)	748 (2,831)	70.0 (32.0)
8556	12 x 30 x 1 (3.7 x 9.1 x 0.3)	2,692 (10,190)	142.0 (64.0)

8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts) See website

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand - See website

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)

## Ultra-Containment Berm® Rapid-Rise Model

Sidewalls stay lowered and out of the way until they are needed

- + Sidewalls remain down during normal operations, loading and unloading — minimizing trip hazards.
- + In the case of a spill, the foam ring around the top perimeter of the Containment Berm rises with the level of spilled liquid.
- + Built-in struts around the perimeter of the Berm provide additional support when the liquid level is high.



+ Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.

+ Custom sizes available.

Copolymer 2000™ Part#	PVC 22 oz. Part#	Dimensions ft. (m) Wall Height: 12 in. (305 mm)	Containment Capacity gal. (L)	Copolymer 2000™ Weight lbs. (kg)	PVC 22 oz. Weight lbs. (kg)
8430	8654	4 x 6 (1.2 x 1.8)	179 (678)	31.0 (14.0)	24.0 (11.0)
8431	8630	6 x 6 (1.8 x 1.8)	269 (1,018)	37.0 (17.0)	30.0 (14.0)
8432	8631	10 x 10 (3.0 x 3.0)	748 (2,831)	69.0 (31.0)	54.0 (24.5)
8437	8656	12 x 26 (3.7 x 7.9)	2,333 (8,831)	151.0 (68.5)	118.0 (54.0)
8433	8664	15 x 50 (4.6 x 15.2)	5,610 (21,234)	302.0 (137.0)	244.0 (111.0)
8434	8666	15 x 66 (4.6 x 20.1)	7,405 (28,028)	388.0 (175.0)	313.0 (142.0)

8670 - All-In-One option (Includes pre-attached Ground Tarp and Track Belts) See website

Options: Ground Tarps, Track Belts, Pullover Covers, Self Bailer, Hose Stand - See website

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)



## Ultra-Containment Berm® Stake Wall Model

Portable secondary containment for drums, tanks, equipment, and vehicles



- + No set-up required — unfold and the sidewalls automatically spring into their vertical position.
- + Sidewalls collapse in either direction and spring back automatically to their upright position.
- + Standard material of construction is Copolymer 2000™ (28 oz.). Other rugged, chemical resistant materials available.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



Part#	Dimensions ft. (m)	Containment Capacity gal. (L)	Weight lbs. (kg)
8208	4 x 6 x 1 (1.2 x 1.8 x 0.3)	179 (678)	38.0 (17.0)
8209	6 x 6 x 1 (1.8 x 1.8 x 0.3)	269 (1,018)	49.0 (21.0)
8210	10 x 10 x 1 (3 x 3 x 0.3)	748 (2,831)	92.0 (42.0)
8211	15 x 50 x 1 (4.6 x 15.2 x 0.3)	5,610 (21,234)	383.0 (174.0)
8212	15 x 66 x 1 (4.6 x 20.1 x 0.3)	7,405 (28,028)	490.0 (222.0)

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)

## Ultra-Global Funnel®



The Ultra-Global Funnel securely fits nearly every 55-gallon tighthead steel or polyethylene drum manufactured throughout the world. Its unique bottom design fits tightly on drums with varying diameters — no more wobbles or drips!



## Ultra-Burp-Free Funnel®



The Burp-Free Funnels feature a built-in vent. So there is no more splashing or “burping” when pouring liquids. The threaded brass insert screws into 2” drum bung or tank cap. The hinged, lockable lid prevents unauthorized access.



Part#	Description	Dimensions in. (mm)	Cap. gal. (L)	Weight lbs. (kg)
0497	Global Funnel	28 dia. x 9 (711.2 x 228.6)	5 (18.9)	12 (5.4)
0499	Global Funnel With Hinged Cover	29 dia. x 11 (736.6 x 279.4)	5 (18.9)	17 (7.7)
0651	Burp-Free Funnel (Standard)	13.4 dia. x 11 (340 x 279)	—	2.0 (1.0)
0656	Burp-Free Funnel (Large)	22 dia. x 11.5 (559 x 292)	—	6.0 (3.0)

## Ultra-Containment Berm® Compact Model

Compact design folds into a tight package – minimal space required to store onboard trucks and hazmat response vehicles

- + Compact, lightweight, portable design — no inflation required.
- + Sidewalls lower quickly to allow drive in/drive out.
- + Standard material of construction is Copolymer 2000™ (28 oz.). Other rugged, chemical resistant materials available.
- + Meets 40 CFR 112 (SPCC) and EPA Container Storage Regulation 40 CFR 264.175 Spill Containment Regulations.



Patents: See [www.ultratechpatents.com](http://www.ultratechpatents.com)

Part#	Dimensions ft. (m)	Containment Capacity gal. (L)	Weight lbs. (kg)
8609	10 x 10 x 1 (3 x 3 x 0.3)	748 (2,831)	72.0 (32.5)
8610	15 x 50 x 1 (4.6 x 15.2 x 0.3)	5,610 (21,234)	317.0 (144.0)
8611	10 x 10 x 1 (3 x 3 x 0.3)	748 (2,831)	72.0 (32.5)
8612	12 x 60 x 1 (3.7 x 18.3 x 0.3)	5,385 (20,384)	391.0 (177.0)
8613	15 x 50 x 1 (4.6 x 15.2 x 0.3)	5,610 (21,234)	317.0 (144.0)
8614	15 x 66 x 1 (4.6 x 20.1 x 0.3)	7,405 (28,028)	472.0 (214.0)

Additional sizes available at [spillcontainment.com/containmentberms](http://spillcontainment.com/containmentberms)

## Ultra-Self Bailer®



Passively filter hydrocarbons from stormwater in outdoor containment products

- + The best protection for non-monitored containment sites.
- + Helps eliminate problems associated with the collection of rainwater in outdoor containment products.
- + Larger or concentrated spills activate “auto-shutoff” mechanism.
- + Manual shutoff valve can be used to secure all draining operations, change out the filter cartridge.



Use with IBC Spill Pallets, Containment Sumps, and other outdoor containment products.

9928

Patents: See [www.ultratechpatents.com](http://www.ultratechpatents.com)

Part#	Size	Dimensions in. (mm)	Material	Flow Rate gal. (L) per hour	Weight lbs. (kg)	Replacement Filter Part#
9935	Standard	28 L x 3.5 dia. (712 x 89)	PVC	7.5 (29)	2.0 (1.0)	9936 (Qty. 2)
9937	Large	36 L x 4.5 dia. (915 x 115)	PVC	22 (84)	6.0 (3.0)	9938 (Qty. 1)
9926	XL	39 L x 6.5 dia. (991 x 166)	PVC	42 (159)	11.0 (5.0)	9927 (Qty. 1)
9928	XXL	43 L x 9 dia. (1,093 x 229)	PVC	55 (209)	16.0 (7.0)	9929 (Qty. 1)

# Ultra-Track Pan® Composite Model



Modular, 20-foot spill containment pans share containment, providing unlimited capacity

- + Easy installation - minimal site preparation (no excavation) required.
- + Constructed with high strength, non-porous, corrosion-resistant fiberglass for years of reliable service.
- + Low-profile: 20' long x 4-7/8" high.
- + Pandrol compatible.
- + Railside gasket sealing system – prevents spills from leaking between track pans and rails.
- + Optional flow-through technology increases containment capacity for larger spills while minimizing cleanup of smaller spills.
- + Optional drainage manifold allows center and side pans to drain to oil/water separators, holding ponds, etc.
- + Drainage manifold comes with clean out port to allow for removal of sludge blockages, etc. Installation requires minimal ballast removal.
- + Optional polyethylene grating package available for safer foot traffic.



System shown includes one Center Pan (Part# 7200) and two Side Pans (Part# 7210)



Optional flow through technology increases containment capacity for larger spills while minimizing cleanup of smaller spills.



Optional polyethylene grating package available for safer foot traffic.



Optional rail side gaskets prevent leaking between rails and Track Pans.

Part#	Description	Dimensions in. (mm)	Containment Capacity gal. (L)	Weight lbs. (kg)
7200	Center Pan	255 x 57.3 x 4.5 (6,477 x 1,448 x 114)	209 (791) With grating: 191 (723)	177 (80) With grating: 191 (723)
7210	Side Pan	255 x 36 x 4.5 (6,477 x 914 x 114)	98 (371) With grating: 89 (337)	100 (45) With grating: 89 (337)

Options: 7220 Drain Manifold Center & Sides · 7223 Drain Manifold Center Only · 7225 Rail Gasket · 0420 Grating

Visit [trackpans.com](http://trackpans.com) for more detailed information.

# Ultra-Overpack®



Screw top Ultra-Overpacks offer the highest UN and DOT certifications available

- + Complies with UN Packaging Group 1 (X-Rating) and are certified for use as DOT Salvage Drums, 49 CFR 173.3 (c). Visit [SpillContainment.com](http://SpillContainment.com) for more regulatory information.
- + Excellent chemical resistance, including acids, caustics, and corrosives.
- + Convenient, "no-tools required" closures are perfect for clean-up and spill response activities.
- + Nestable design and low tare weight allow convenient storage and reduced transportation costs.



Part#	Model	Capacity gal. (L)	Top Outside Dia. in. (mm)	Outside Height in. (mm)	Weight lbs. (kg)
0580	95 Gallon	95 (360)	32.3 (820)	41.3 (1,049)	48.0 (22.0)
0584	95 Wheeled	95 (360)	32.3 (820)	48.5 (1,232)	58.0 (26.0)
0570	95 Recycled	95 (360)	32.3 (820)	41.3 (1,049)	48.0 (22.0)
0582	65 Gallon	65 (247)	29 (737)	36.3 (921)	40.0 (18.0)
0585	30 Gallon	30 (113.5)	22.9 (581)	30.1 (765)	15.0 (7.0)
0587	20 Gallon	20 (76)	21.3 (552)	19.3 (489)	12.0 (5.5)

# Ultra-Spill Berm®



Temporary berm seals off spills from the environment, nearby drains, and doorways

- + Unique, urethane material "weeps" into small cracks and crevices to seal off liquid flow.
- + Spill Berm is non-absorbing and is easily cleaned for repeated use.
- + Helps comply with NPDES and SPCC.



Standard Model



Plus Model

Part#	Model	Color	Dimensions in (mm)	Weight lbs. (kg)
2100	Standard	Orange	120 x 4 x 2.3 (3,048 x 101.6 x 57.2)	31.0 (14.0)
2054	Plus	Orange	60 x 4 x 4.5 (1,524 x 101.6 x 114.3)	16.0 (7.0)
2050	Standard	Black	120 x 4 x 2.3 (3,048 x 101.6 x 57.2)	31.0 (14.0)



## Ultra-Drain Seal®



Stop spills from going down the drain

- + Reinforcing mesh is “sandwiched” between layers of polyurethane — increases durability and resistance to tearing.
- + Unique, urethane construction allows the pad to deform and seal off most drains — temporarily “seals” to any smooth surface.
- + A valuable addition to any emergency response plan, spill kit, SPCC, or stormwater management program.
- + Unlike some alternative products, BOTH sides will quickly seal drains — there is no specified “top” or “bottom.”



2130



2134

Patents: See [www.ultratechpatents.com](http://www.ultratechpatents.com)

Part#	Shape	Dimensions in. (mm)	Weight lbs. (kg)
2127	Square	24 x 24 x .4 (610 x 610 x 10)	8.0 (3.5)
2130	Square	36 x 36 x .4 (915 x 915 x 10)	20.0 (9.0)
2131	Square	42 x 42 x .4 (1,067 x 1,067 x 10)	23.0 (10.5)
2132	Square	48 x 48 x .4 (1,220 x 1,220 x 10)	36.0 (17.0)
2133	Square	54 x 54 x .4 (1,372 x 1,372 x 10)	41.0 (18.5)
2134	Circular	12 dia. x .4 (305 x 10)	3.0 (1.5)
2136	Circular	30 dia. x .4 (762 x 10)	11.0 (5.0)

More sizes and Clear Models available. · Wall Mounts available.

## Ultra-Filter Sock®

Stop harmful substances from entering the stormwater system

- + Use in front of storm drains, around downspouts, in gullies, and ditches.
- + Woven polymer casing allows water to pass through quickly while filtration media inside removes pollutants.
- + Available in 9-foot lengths. Units can be overlapped for longer coverage.
- + Available with different types of media depending on which pollutant is present.



Part#	Description	Dimensions in. (mm)	Weight lbs. (kg)
9453	Activated Carbon	108 x 7 x 4 (2,743 x 178 x 102)	40.0 (18.0)
9455	Sorb 44	108 x 7 x 4 (2,743 x 178 x 102)	15.0 (7.0)
9457	Sediment Removal	108 x 7 x 4 (2,743 x 178 x 102)	40.0 (18.0)
9456	Phos Filter	108 x 7 x 4 (2,743 x 178 x 102)	66.0 (30.0)
9454	Heavy Metal Removal	108 x 7 x 4 (2,743 x 178 x 102)	35.0 (16.0)

For full details on 5 Year Warranty, please visit [spillcontainment.com/warranty](http://spillcontainment.com/warranty)

## Ultra-Drain Guard®



Keep sediment and other pollutants from entering the water system with Ultra-Drain Guard catch basin inserts

- + Easily installs in storm drains up to 30" x 40" and filters stormwater waste before it becomes a problem in the water system.
- + Ideal for use in industrial facilities, construction sites, and parking lots where stormwater runoff is likely to carry oil, eroded soil, debris, and fuel contaminants.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) and TMDL requirements - All Models.



9217

Ultra-Drain Guards®  
Oil & Sediment Plus



Ultra-Drain Guards®  
Oil & Sediment Model



Patents: See [www.ultratechpatents.com](http://www.ultratechpatents.com)

Part#	Description	Dimensions in. (mm)	Performance	Weight lbs. (kg)
9217	Oil & Sediment (1-Pack)	48 x 36 x 18 (1,220 x 915 x 458)	Up to .87 gals. (3.5 L) of oil and up to 40 lbs. (18 kg) of sediment	1.0 (0.5)
9218	Oil & Sediment (10-Pack)	48 x 36 x 18 (1,220 x 915 x 458)	Up to .87 gals. (3.5 L) of oil and up to 40 lbs. (18 kg) of sediment	1.0 (0.5)
9219	Oil & Sediment Plus Model (1-Pack)	48 x 36 x 18 (1,220 x 915 x 458)	Up to 1.38 gallons (5L) of oil and up to 40 lbs. (18 kg) of sediment	2.0 (1.0)
9220	Oil & Sediment Plus Model (10-Pack)	48 x 36 x 18 (1,220 x 915 x 458)	Up to 1.38 gallons (5L) of oil and up to 40 lbs. (18 kg) of sediment	2.0 (1.0)

## Ultra-Dewatering Bag®



Contain sediment and oil pumped out during dewatering operations

- + Retains both oil and sediment, offering a combination of benefits not available in alternative dewatering bags.
- + Accommodates up to 4" discharge hose.
- + Helps comply with NPDES, 40 CFR 122.26 (1999) when used as Best Management Practice in Stormwater Pollution Prevention Plans.



9724-O/S

Part#	Dimensions ft. (mm)	Capacity cu. ft. (L)	Weight lbs. (kg)
9729-OS	4 x 3 x 0 (1.2 x .9 x 0)	12 (340)	2 (.9)
9724-OS	6 x 6 (1,829 x 1,829)	18 (510)	5.0 (2.5)
9723-OS	8 x 8 x 0 (2.4 x 2.4 x 0)	64 (1,812)	10 (4.54)
9725-OS	10 x 15 (3,048 x 4,572)	150 (4,247)	21.0 (9.5)
9727-OS	15 x 15 (4,572 x 4,572)	225 (6,371)	30.0 (14.0)